

SELF DRIVE ACCESS PLATFORM



17.10m (56ft 1in) Working height

8.70m (28ft 7in) Working outreach

Weight Saving Design Lower cost transportation & better fuel economy on site

Telescopic Upper Boom Greater accuracy when positioning the platform

Bi-Energy Available Optimises utilisation

Hydraulic Outriggers Quick & easy to set up

Fully Proportional Hydraulic Controls

Simple, reliable & easy to maintain

Platform Rotation

Better access to applications



(()



The Nifty **SD170** combines the best of our self-propelled and trailer mounted ranges. It offers the same staggering reach capabilities as the **Nifty 170** but with the versatility of a robust yet very lightweight drivable base. This allows the operator to manoeuvre, set up and operate this machine without leaving the platform, especially on uneven surfaces.

SAFETY FEATURES

- CE Mark
- Pressure sensitive outriggers
- Audible & visual alarms
- Dual controls (platform & base)
- Manual descent with hand-pump
- Lock valves on all hydraulic cylinders







The **SD170's** outstanding reach makes it ideal for construction site work.





Also available trailer mounted. See **Nifty 170** specification sheet.



Rough terrain tyres as standard and the 4WD option allow the **SD170** to manoeuvre easily over a wide range of site conditions.

SPECIFICATIONS

Working Height	17.10m	56ft 1in
Platform Height	15.10m	49ft 6in
Working Outreach	8.70m	28ft 7in
Slew	360°	
Width - Travelling	1.60m	5ft 3in
- Working	4.40m	14ft 5in
Height	2.10m	6ft 11in
Length	5.60m	18ft 4in
Minimum Weight	2750kg*	6000lbs*
Turning Radius - Inside	2.25m	7ft 5in
- Outside	5.20m	17ft
Platform Rotation	100°	
Platform Capacity	200kg	440lbs
Platform Size	1.10m x 0.65m	3ft 7in x 2ft 2in
Drive Speed	5.0kph	3.1mph
Gradeability	25% (2x4)	30% (4x4)
Control System	Fully Proportional Hydraulic	
Power Options	Battery Only	
	Petrol or Diesel Only	
	Bi-Energy (Engine and Battery)	
* Weights may vary according to specification	/ nower ontions please confirm before	ore ordering

* Weights may vary according to specification / power options, please confirm before ordering.

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.



NIFTYLIFT LTD atforms. Fingle Drive Stonebridge Milton Keynes MK13 0ER England www.niftylift.com e-mail: info@niftylift.com Tel.: +44 (0)1908 223456 Fax.: +44 (0)1908 312733



IS-04